

In the Claims:

1. (Withdrawn) A light emitting diode according to Claim 62:
wherein the first face is patterned to define, in cross-section, a plurality of pedestals that extend into the substrate from the first face towards the second face.
2. (Withdrawn) A light emitting diode according to Claim 1 further comprising:
a mounting support on the diode region, opposite the substrate, the mounting support being configured to support the diode region such that the light that is emitted from the diode region into the substrate is emitted from the plurality of pedestals, upon application of voltage across the diode region.
3. (Withdrawn) A light emitting diode according to Claim 1 further comprising:
a mounting support on the first face, opposite the diode region, the mounting support being configured to support the first face.
4. (Withdrawn) A light emitting diode according to Claim 2 wherein the
reflector layer is configured to reflect light that is emitted from the diode region back into the diode region, through the substrate that is transparent to optical radiation in the predetermined wavelength range and from the plurality of pedestals, upon application of voltage across the diode region.
5. (Withdrawn) A light emitting diode according to Claim 3 further comprising:
a reflector between the mounting support and the first face, that is configured to reflect light that is emitted from the first face back into the substrate, upon application of voltage across the diode region.
6. (Withdrawn) A light emitting diode according to Claim 4 further comprising:
a transparent electrode between the diode region and the reflector.
7. (Withdrawn) A light emitting diode according to Claim 5 further comprising a
transparent electrode between the first face and the reflector.

8. (Withdrawn) A light emitting diode according to Claim 4 wherein the reflector layer comprises a layer of at least one reflective metal.

9. (Withdrawn) A light emitting diode according to Claim 6 wherein the transparent electrode comprises a layer of nickel/gold, nickel oxide/gold, nickel oxide/platinum, titanium and/or titanium/gold.

10. (Withdrawn) A light emitting diode according to Claim 4: wherein the second barrier layer comprises a barrier region between the reflector layer and the mounting support; and

wherein the second bonding layer comprises a bonding region between the barrier region and the mounting support.

11. (Withdrawn) A light emitting diode according to Claim 5: wherein the first barrier layer comprises a barrier region between the reflector and the mounting support; and

wherein the first bonding layer comprises a bonding region between the barrier region and the mounting support.

12. (Withdrawn) A light emitting diode according to Claim 10 wherein the bonding region comprises gold, indium, solder and/or braze.

13. (Withdrawn) A light emitting diode according to Claim 11 wherein the bonding region comprises gold, indium, solder and/or braze.

14. (Withdrawn) A light emitting diode according to Claim 1 further comprising: an optical element adjacent the first face, opposite the diode region.

15. (Withdrawn) A light emitting diode according to Claim 1 wherein the first face of the substrate includes therein at least one groove that defines, in cross-section, the plurality of pedestals in the substrate.

16. (Withdrawn) A light emitting diode according to Claim 15 wherein the pedestals are triangular pedestals.

17. (Withdrawn) A light emitting diode according to Claim 15 wherein the grooves include tapered and/or curved sidewalls.

18. (Withdrawn) A light emitting diode according to Claim 15 wherein the grooves include a beveled and/or curved floor.

19. (Withdrawn) A light emitting diode according to Claim 17 wherein the grooves include a beveled and/or curved floor.

20. (Withdrawn) A light emitting diode according to Claim 15 wherein the first and second faces of the substrate comprise square perimeters.

21. (Withdrawn) A light emitting diode according to Claim 15 wherein the first face of the substrate comprises a textured surface.

22. (Withdrawn) A light emitting diode according to Claim 1 wherein the first face of the substrate includes therein an array of via holes that defines, in cross-section, the plurality of pedestals in the substrate.

23. (Withdrawn) A light emitting diode according to Claim 22 wherein the via holes include tapered and/or curved sidewalls.

24. (Withdrawn) A light emitting diode according to Claim 22 wherein the via holes include a flat, beveled and/or curved floor.

25. (Withdrawn) A light emitting diode according to Claim 23 wherein the via holes include a flat, beveled and/or curved floor.

26. (Withdrawn) A light emitting diode according to Claim 22 wherein the first and second faces of the substrate comprise square perimeters.

27. (Withdrawn) A light emitting diode according to Claim 22 wherein the first face of the substrate comprises a textured surface.

28. (Withdrawn) A light emitting diode according to Claim 22 wherein the array of via holes comprises an array of tapered and/or curved via holes.

29. (Withdrawn) A light emitting diode according to Claim 1 wherein the diode region comprises a peripheral portion, at least one central portion that is enclosed by the peripheral portion and at least one emission region that is confined to within the at least one central portion and does not extend onto the peripheral portion.

30. (Withdrawn) A light emitting diode according to Claim 1 further comprising: a plurality of emission regions on the diode region, a respective one of which is confined to within a respective one of the pedestals and does not extend beyond the respective one of the pedestals.

31. (Withdrawn) A light emitting diode according to Claim 15 further comprising:
a plurality of electrodes on the diode region, a respective one of which is confined to within a respective one of the pedestals and does not extend beyond the respective one of the pedestals.

32. (Withdrawn) A light emitting diode according to Claim 22 further comprising:
at least one electrode on the diode region that does not overlap the via holes.

33. (Withdrawn) A light emitting diode according to Claim 1, wherein the substrate comprises silicon carbide and wherein the diode region comprises gallium nitride.

34. (Withdrawn) A light emitting diode according to Claim 1 wherein the first face has smaller surface area than the second face; and

the diode region includes an emission region that is confined to within the smaller surface area of the first face.

35. (Withdrawn) A light emitting diode according to Claim 34 wherein the emission region comprises a mesa.

36. (Withdrawn) A light emitting diode according to Claim 34 wherein the first face of the substrate comprises a textured surface.

37. (Withdrawn) A light emitting diode according to Claim 35 further comprising a transparent electrode on at least a portion of the mesa.

38. (Withdrawn) A light emitting diode according to Claim 34 wherein the substrate is a silicon carbide substrate that is transparent to optical radiation in a predetermined wavelength range and wherein the diode region is configured to emit light in the predetermined wavelength range.

39. (Withdrawn) A light emitting diode according to Claim 62 wherein the first face has smaller surface area than the second face; the light emitting diode further comprising a mounting support on the diode region, opposite the substrate.

40. (Withdrawn) A light emitting diode according to Claim 39 wherein the substrate is transparent to optical radiation in a predetermined wavelength range and wherein the diode region is configured to emit light in the predetermined wavelength range into the substrate that is transparent to the optical radiation in the predetermined wavelength range, upon application of voltage across the diode region.

41. (Withdrawn) A light emitting diode according to Claim 40 wherein the mounting support is further configured to support the diode region such that the light that is emitted from the diode region into the substrate that is transparent to optical radiation in the

predetermined wavelength range, is emitted from the first face, upon application of voltage across the diode region.

42. (Withdrawn) A light emitting diode according to Claim 41 wherein the reflector layer is configured to reflect light that is emitted from the diode region back into the diode region, through the substrate that is transparent to optical radiation in the predetermined wavelength range and from the first face, upon application of voltage across the diode region.

43. (Withdrawn) A light emitting diode according to Claim 42 further comprising:

a transparent electrode between the diode region and the reflector layer.

44. (Withdrawn) A light emitting diode according to Claim 42 further comprising:

wherein the second barrier layer is between the reflector layer and the mounting support; and

wherein the second bonding layer is between the barrier layer and the mounting support.

45. (Withdrawn) A light emitting diode according to Claim 44 wherein the bonding region comprises gold, indium, solder and/or braze.

46.-61. (Canceled)

62. (Original) A light emitting diode comprising:
a substrate having first and second opposing faces, the first face having smaller surface area than the second face;

a diode region on the second face;

a first ohmic layer on the first face opposite the diode region;

an adhesion layer on the first ohmic layer opposite the substrate;

a first barrier layer on the adhesion layer opposite the first ohmic layer;

a first bonding layer on the first barrier layer opposite the adhesion layer;

a second ohmic layer on the diode region opposite the substrate;
a reflector layer on the second ohmic layer, opposite the diode region;
a second barrier layer on the reflector layer opposite the second ohmic layer; and
a second bonding layer on the second barrier layer opposite the reflector layer.

63. (Withdrawn) A light emitting diode according to Claim 62 further comprising a mounting support on the second bonding layer opposite the second barrier layer.

64. (Original) A light emitting diode according to Claim 62 wherein the second ohmic layer comprises a second ohmic and reflector layer.

65. (Original) A light emitting diode according to Claim 62 wherein the first ohmic layer comprises a reflective metal.

66. (Original) A light emitting diode according to Claim 62 wherein the adhesion layer comprises titanium.

67. (Original) A light emitting diode according to Claim 62 wherein the first barrier layer comprises platinum.

68. (Original) A light emitting diode according to Claim 62 wherein the first bonding layer comprises gold.

69. (Original) A light emitting diode according to Claim 62 wherein the second ohmic layer comprises nickel/gold, nickel oxide/gold, nickel oxide/platinum, titanium and/or titanium/gold.

70. (Original) A light emitting diode according to Claim 62 wherein the reflector layer comprises silver and/or aluminum.

71. (Original) A light emitting diode according to Claim 62 wherein the second barrier layer comprises nickel, nickel/vanadium and/or titanium/tungsten.

72. (Original) A light emitting diode according to Claim 62 wherein the second bonding layer comprises gold, indium, solder and/or braze.

73. (Original) A light emitting diode according to Claim 62 wherein the first ohmic layer, the adhesion layer, the first barrier layer and the first bonding layer each comprises a central portion and at least one finger that extends from the central portion.

74. (Original) A light emitting diode comprising:
a substrate having first and second opposing faces, the first face having smaller surface area than the second face;
a diode region on the second face;
a first layer comprising silver and/or aluminum on the first face opposite the diode region;
a second layer comprising titanium on the first layer opposite the substrate;
a third layer comprising platinum on the second layer opposite the first layer;
a fourth layer comprising gold on the third layer opposite the second layer;
a fifth layer comprising nickel/gold, nickel oxide/gold, nickel oxide/platinum, titanium and/or titanium/gold on the diode region opposite the substrate;
a sixth layer comprising silver and/or aluminum on the fifth layer, opposite the diode region;
a seventh layer comprising nickel, nickel/vanadium and/or titanium/tungsten on the sixth layer opposite the fifth layer; and
an eighth layer comprising gold, indium, solder and/or braze on the seventh layer opposite the sixth layer.

75. (Withdrawn) A light emitting diode according to Claim 74 further comprising a mounting support on the eighth layer opposite the seventh layer.

76. (Original) A light emitting diode comprising:
a substrate having first and second opposing faces, the first face having smaller surface area than the second face;

a diode region on the second face;
a first adhesion layer on the first face opposite the diode region;
a first barrier layer on the first adhesion layer opposite the substrate;
a first bonding layer on the first barrier layer opposite the first adhesion layer;
an ohmic layer on the diode region opposite the substrate;
a reflector layer on the ohmic layer opposite the diode region;
a second adhesion layer on the reflector layer opposite the ohmic layer;
a second barrier layer on the second adhesion layer opposite the reflector layer; and
a second bonding layer on the second barrier layer opposite the second adhesion layer.

77. (Withdrawn) A light emitting diode according to Claim 76 further comprising a mounting support on the first bonding layer opposite the first barrier layer.

78. (Original) A light emitting diode according to Claim 76 wherein the ohmic layer comprises an ohmic and reflector layer.

79. (Original) A light emitting diode according to Claim 76 wherein the first adhesion layer comprises titanium.

80. (Original) A light emitting diode according to Claim 76 wherein the first barrier layer comprises platinum.

81. (Original) A light emitting diode according to Claim 76 wherein the first bonding layer comprises gold.

82. (Original) A light emitting diode according to Claim 76 wherein the ohmic layer comprises nickel/gold, nickel oxide/gold, nickel oxide/platinum, titanium and/or titanium/gold.

83. (Original) A light emitting diode according to Claim 76 wherein the reflector layer comprises silver and/or aluminum.

84. (Original) A light emitting diode according to Claim 76 wherein the second adhesion layer comprises titanium.

85. (Original) A light emitting diode according to Claim 76 wherein the second barrier layer comprises platinum.

86. (Original) A light emitting diode according to Claim 76 wherein the second bonding layer comprises gold.

87. (Original) A light emitting diode comprising:

- a substrate having first and second opposing faces, the first face having smaller surface area than the second face;
- a diode region on the second face;
- a first layer comprising titanium on the first face opposite the diode region;
- a second layer comprising platinum on the first layer opposite the substrate;
- a third layer comprising gold on the second layer opposite the first layer;
- a fourth layer comprising nickel/gold, nickel oxide/gold, nickel oxide/platinum, titanium and/or titanium/gold on the diode region opposite the substrate;
- a fifth layer comprising silver and/or aluminum on the fourth layer opposite the diode region;
- a sixth layer comprising titanium on the fifth layer opposite the fourth layer;
- a seventh layer comprising platinum on the sixth layer opposite the fifth layer; and
- an eighth layer comprising gold on the seventh layer opposite the sixth layer.

88. (Withdrawn) A light emitting diode according to Claim 88 further comprising a mounting support on the third layer opposite the second layer.

89. (Withdrawn) A light emitting diode according to Claim 62:
wherein the substrate comprises a compensated, colorless silicon carbide substrate having first and second opposing faces; and

wherein the diode region comprises a gallium nitride-based diode region on the second face that is configured to emit light into the substrate upon application of voltage across the diode region.

90. (Withdrawn) A light emitting diode according to Claim 89 further comprising:

a mounting support on the diode region, opposite the substrate, the mounting support being configured to support the diode region such that the light that is emitted from the diode region into the substrate, is emitted from the substrate, upon application of voltage across the diode region.

91. (Withdrawn) A light emitting diode according to Claim 89 further comprising:

a mounting support on the first face, opposite the diode region, the mounting support being configured to support the first face.

92. (Withdrawn) A light emitting diode according to Claim 90 wherein the reflector layer is configured to reflect light that is emitted from the diode region back into the diode region, through the substrate and from the substrate, upon application of voltage across the diode region.

93. (Withdrawn) A light emitting diode according to Claim 91 further comprising:

a reflector between the mounting support and the first face, that is configured to reflect light that is emitted from the first face back into the substrate, upon application of voltage across the diode region.

94. (Withdrawn) A light emitting diode according to Claim 92 further comprising:

a transparent electrode between the diode region and the reflector.

95. (Withdrawn) A light emitting diode according to Claim 93 further comprising a transparent electrode between the first face and the reflector.

96. (Withdrawn) A light emitting diode according to Claim 92 wherein the reflector layer comprises a layer of at least one reflective metal.

97. (Withdrawn) A light emitting diode according to Claim 94 wherein the transparent electrode comprises a layer of nickel/gold, nickel oxide/gold, nickel oxide/platinum, titanium and/or titanium/gold.

98. (Withdrawn) A light emitting diode according to Claim 92:
wherein the second barrier layer comprises a barrier region between the reflector layer and the mounting support; and
wherein the second bonding layer comprises a bonding region between the barrier region and the mounting support.

99. (Withdrawn) A light emitting diode according to Claim 93:
wherein the first barrier layer comprises a barrier region between the reflector and the mounting support; and
wherein the first bonding layer comprises a bonding region between the barrier region and the mounting support.

100. (Withdrawn) A light emitting diode according to Claim 98 wherein the bonding region comprises gold, indium, solder and/or braze.

101. (Withdrawn) A light emitting diode according to Claim 99 wherein the bonding region comprises gold, indium, solder and/or braze.

102. (Withdrawn) A light emitting diode according to Claim 89 further comprising:
an optical element adjacent the first face, opposite the diode region.

103. (Withdrawn) A light emitting diode according to Claim 89 wherein the first face of the substrate includes therein at least one groove that defines, in cross-section, a plurality of pedestals that extend into the substrate from the first face towards the second face.

104. (Withdrawn) A light emitting diode according to Claim 103 wherein the pedestals are triangular pedestals.

105. (Withdrawn) A light emitting diode according to Claim 103 wherein the grooves include tapered and/or curved sidewalls.

106. (Withdrawn) A light emitting diode according to Claim 103 wherein the grooves include a beveled and/or curved floor.

107. (Withdrawn) A light emitting diode according to Claim 105 wherein the grooves include a beveled and/or curved floor.

108. (Withdrawn) A light emitting diode according to Claim 103 wherein the first and second faces of the substrate comprise square perimeters.

109. (Withdrawn) A light emitting diode according to Claim 103 wherein the first face of the substrate comprises a textured surface.

110. (Withdrawn) A light emitting diode according to Claim 89 wherein the first face of the substrate includes therein an array of via holes that defines, in cross-section, a plurality of pedestals that extend into the substrate from the first face towards the second face.

111. (Withdrawn) A light emitting diode according to Claim 110 wherein the via holes include tapered and/or curved sidewalls.

112. (Withdrawn) A light emitting diode according to Claim 110 wherein the via holes include a flat, beveled and/or curved floor.

113. (Withdrawn) A light emitting diode according to Claim 111 wherein the via holes include a flat, beveled and/or curved floor.

114. (Withdrawn) A light emitting diode according to Claim 110 wherein the first and second faces of the substrate comprise square perimeters.

115. (Withdrawn) A light emitting diode according to Claim 110 wherein the first face of the substrate comprises a textured surface.

116. (Withdrawn) A light emitting diode according to Claim 110 wherein the array of via holes comprises an array of tapered and/or curved via holes.

117. (Withdrawn) A light emitting diode according to Claim 89 wherein the diode region comprises a peripheral portion, at least one central portion that is enclosed by the peripheral portion and at least one emission region that is confined to within the at least one central portion and does not extend onto the peripheral portion.

118. (Withdrawn) A light emitting diode according to Claim 89 further comprising:

a plurality of emission regions on the diode region, a respective one of which is confined to within a respective one of the pedestals and does not extend beyond the respective one of the pedestals.

119. (Withdrawn) A light emitting diode according to Claim 103 further comprising:

a plurality of electrodes on the diode region, a respective one of which is confined to within a respective one of the pedestals and does not extend beyond the respective one of the pedestals.

120. (Withdrawn) A light emitting diode according to Claim 110 further comprising:

at least one electrode on the diode region that does not overlap the via holes.

121. (Withdrawn) A light emitting diode comprising:
a substrate having first and second opposing faces;
a gallium nitride-based diode region on the second face that is configured to emit light into the substrate, upon application of voltage across the diode region; and
means for extracting from the substrate, at least some of the light that is emitted into the substrate by the diode region.

122. (Withdrawn) A light emitting diode according to Claim 121 wherein the substrate comprises silicon carbide and wherein the means for extracting comprises means for compensating dopants in the silicon carbide to provide a colorless silicon carbide substrate.

123. (Withdrawn) A light emitting diode according to Claim 121 wherein the means for extracting comprises means for patterning the substrate to define, in cross section, a plurality of pedestals that extend into the substrate from the first face towards the second face.

124.-148. (Canceled)